

UNI-T® UT350 SERIES Sound Level Meters

UT 351 ■ UT352



■ UT351



■ UT352

SPECIFICATIONS



Specifications	Range	Best Accuracy	
		UT351	UT352
Model	30~80dB	±1.5dB	±1.5dB
Range	50~100dB	±1.5dB	±1.5dB
	60~110dB	±1.5dB	±1.5dB
	80~130dB	±1.5dB	±1.5dB
	31.5Hz~8000Hz	✓	✓
Frequency	A&C	✓	✓
Frequency Weighting	FAST: 8 Times/s	✓	✓
Sample Rate	SLOW: 1 Times/s	✓	✓
Features			
Analogue Outputs	AC:0.707Vrms full scale;Output impedance: around 600Ω	✓	✓
	DC:2Vrms full scale;10mV/dB;Output impedance: around 100Ω	✓	✓
Data Hold		✓	✓
Auto Power Off		✓	✓
Low Battery Indication	≤4.8V	✓	✓
MAX Mode		✓	✓
MIN Mode		✓	✓
Data Logging			63
High Alarm	Display "OVER"	✓	✓
Lower Alarm	Display "UNDER"	✓	✓
LCD Backlight		✓	✓
Analogue Bar Graph	30~130dB	✓	✓

GENERAL CHARACTERISTICS

Power	1.5V Batteries (LR6) × 4
LCD Size	53mm × 41mm
Product Color	Red and Grey
Product Net Weight	330g
Product Size	273mm × 70mm × 39mm
Standard Accessories	Batteries,Windscreen, Leather Cas
Standard Individual Packing	Gift Box,English Manual
Standard Quantity Per Carton	30 PCs
Standard Carton Measurement	670mm × 385mm × 300mm (0.077 CBM Per Standard Carton)
Standard Carton Gross Weight	18 Kg